



ProVantage Kraftliner

Benefits

- Exceptional Burst strength for better product protection.
- Optimum runnability with reduced waste
- Fewer failures and fewer stoppages
- Stable and uniform moisture and glue absorption properties
- 100% recyclable for environmentally sound packaging

End-uses

- **Food & beverage packaging:** Fruit & vegetable packaging, Agricultural produce, High-humidity & extreme-climate storage
- **Industrial packaging:** Automotive industry, Consumer durables, Chemicals, Furniture
- **Luxury packaging:** Electronics, cigarettes & tobacco
- **Heavy-duty packaging**



Food Contact	ISO 9001	ISO 14001	ISO 45001	FSC®	PEFC™
•	•	•	•	•	•

Typical Values**

Properties	Method	Unit of measure	Substance (lb/1000 ft ²)												
			20.5	22.5*	25.6*	27.7*	30.7	32.8	34.8*	38.1*	41.0	46.1	51.2	56.3	61.4
Moisture	ISO 287	%	7.8												
Bursting strength	ISO 2758	lbf/in ²	66.7	76.9	84.1	88.5	98.6	102	106	115	123	133	140	152	171
SCT _{CD}	ISO 9895	lbf/inch	11.4	13.1	14.3	15.4	17.1	18.3	19.4	21.1	22.8	25.1	28.6	30.8	34.3
Tensile stiffness index _{MD}		kNm/g	12						11						
Tensile stiffness index _{CD}		kNm/g	5												
Cobb ₆₀ (top)	ISO 535	g/m ²	30												
Cobb ₆₀ (bottom)			70												
Dennison test	TAPPI 459 om-08	No.	18												
Gurley	ISO 5636-5	s	max. 150												



Issued from 01.01.2021,
latest version available on
www.mondigroup.com

Test conditions:
Typical values after conditioning,
measured at 50 ± 2% RH and 23 ± 1°C (ISO 187 : 1990)

*ECO Premium Service, fast delivery option
**computed, based on SI units

WWF's Environmental Paper Company Index: Mondi's constant high packaging score increased from 73.7% in 2013 to 85.7% in 2019.